



MBB Half-cell Monofacial Black-frame Module (60)

TW445~465PERC M10-120-H

PRODUCT FEATURES



High Power Output
Low LCOE



Maximum Power
465W*




High
Reliability



Low
LID

POWER WARRANTY

1st year <2%, 0.55% power degradation per year from 2 to 25 years



12-year warranty for materials



25-year warranty for linear power output

MANAGEMENT SYSTEM AND PRODUCT CERTIFICATION

ISO9001: 2015/Quality Management System

ISO14001: 2015/Environment Management System


ISO45001: 2018/Occupational Health and Safety



Front



Rear



Electrical Characteristics (STC)

Module type: TW***MAP-120-H-S

Maximum power: Pmax (W)	445	450	455	460	465
Open circuit voltage: Voc (V)	41.04	41.21	41.38	41.55	41.72
Short circuit current: Isc (A)	13.79	13.84	13.89	13.94	13.99
Voltage at maximum power point: Vmp (V)	33.67	33.83	33.99	34.15	34.31
Current at maximum power point: Imp (A)	13.22	13.30	13.39	13.47	13.55
Module efficiency: η (%)	20.6	20.8	21.0	21.3	21.5

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass1.5, Measuring tolerance: $\pm 3\%$

Electrical Characteristics (NOCT)

Maximum power: Pmax(W)	336.7	340.5	344.3	348.1	351.9
Open circuit voltage: Voc (V)	38.93	39.11	39.30	39.49	39.68
Short circuit current: Isc (A)	10.88	10.91	10.95	10.97	11.01
Voltage at maximum power point: Vmp (V)	32.15	32.37	32.59	32.81	33.02
Current at maximum power point: Imp (A)	10.47	10.52	10.56	10.61	10.65

NMOT: Irradiance 800W/m², Ambient Temperature 20 °C, Air Mass1.5, Wind Speed 1m/s

Mechanical Parameters

Cells	P-TPC
Orientation	120 (6×20)
Size	1908±2×1134±2×35mm
Weight	24.2kg
Glass	3.2mm AR coated heat strengthened glass
Backsheet	White
Frame	Anodized aluminum alloy frame
Junction Box	IP68, 3 diodes
Cable	+400mm, -200mm or ± 1200 mm, length can be customized
Connector	MC4 Compatible or MC4 original
Wind/Snow Load	2400Pa/5400Pa
Packaging	31pcs per pallet , 744pcs per 40'HC


Operating Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	25A
Power Output Tolerance	0~+5W

Temperature Ratings

Temperature Coefficient (Pmax)	-0.34%/°C
Temperature Coefficient (Voc)	-0.27%/°C
Temperature Coefficient (Isc)	+0.045%/°C
NMOT	45±2°C

Drawings (Unit: mm)



Email: sales@tongwei.com Web: www.tongwei.com.cn Add: 888 Changning Avenue, High-tech Zone, Hefei City, Anhui Province

With technological progress and product updates, there may be deviations between the technical parameters of Tongwei's module products and the technical parameters contained in this specification, and Tongwei Solar has the right to adjust the technical parameters at any time without notifying the customer, the final interpretation of the technical specification is vested in Tongwei Solar.